



DataSheet

Series	Open Frame Enclosed Encapsulated	Pin Connection Type	Output Power (W)		Input Voltage (VAC)	Single Output Dual Output Triple Output	Output Voltage												Eff. (%)	Leakage Current (µA)	Isolation Voltage (VAC)	Dimensions (Inch)		
			Con.	Peak			3.3 Vout	5.0 Vout	7.5 Vout	9.0 Vout	12 Vout	15 Vout	18 Vout	24 Vout	28 Vout	36 Vout	48 Vout	53 Vout				54 Vout	L	W
MSC15		● ●	15		85 - 264	●	● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●	89	75	4000	2.82	1.14	0.82											
MSD30		● ●	30	● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●		91.5	100	3.95	1.50		1.00													
MSD40		● ●	40	● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●		93	75	4.30	2.20		1.20													
MSD65		● ●	65	● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●		93.5	75	4.30	2.20		1.20													
MAC15	●		15	● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●		89	75	2.61	1.00		0.62													
MAD30	●		30	● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●		91.5	100	3.34	1.36		0.77													
MAD40 Single	● ●		40	● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●		93	75	3.00	2.00		0.94													
MAD65 Single	● ●		65	● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●		93.5	75	3.00	2.00		0.94													
MAD40 Multi	● ●		40	● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●		90	75	3.50	2.00		0.98													
MAD65 Multi	● ●		65	● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●		90.5	75	3.50	2.00		0.98													
MAD100	● ●		100	● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●		92	75	3.00	2.00		1.16													
MAF150	● ●		150	● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●		92	100	4.00	2.00		1.16													
MAD180	● ●		180	220		● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●	94	100	3.00		2.00	1.24												
MAF300	● ●		300	360		● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●	93	100	4.00		2.09	1.26												
MAH450	● ●		450	● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●		94	100	5.00	3.00		1.58													

【お問い合わせ先】

JEMCO

株式会社ジェムコ

大阪本社 TEL : 06-6338-8566

東京 TEL : 080-6449-9194

名古屋 TEL : 0587-96-1970

URL : <http://www.jemc.co.jp/>

E-Mail : inf@jemc.co.jp



DataSheet	Series	Footprint	Output Power (W)	Input Ratio		Input Voltage (VDC)	Single Output	Dual Output	Output Voltage									Eff. (%)	Leakage Current (μA)	Clearance Creepage (mm)	Isolation Voltage	Dimensions (Inch)				
				4:1	2:1				3.3 Vout	5.0 Vout	5.1 Vout	9.0 Vout	12 Vout	15 Vout	24 Vout	±5 Vout	±12 Vout					±15 Vout	L	W	H	
↓	MPU01	SIP-9	1			4.5 – 5.5 9.6 – 14.4 12 – 18 19.2 – 28.8	● ●	● ●			● ●			● ●	● ●	● ●	● ●	85	2	8	2MOPP 5000 VAC	0.77	0.49	0.39		
↓	MPU02		2			4.5 – 7 9.6 – 14.4 12 – 18 19.2 – 28.8	● ●	● ●			● ●			● ●	● ●	● ●	● ●	84								
↓	MPL02	SIP-8	2	●		4.5 – 12 9 – 18 18 – 36	● ●	● ●			● ●			● ●	● ●	● ●	85	0.86				0.39	0.40			
↓	MPS02	SMD-16 DIP-16	2	●		4.5 – 12 9 – 18	● ●	● ●			● ●			● ●	● ●	● ●	82	0.95				0.57	0.40			
↓	MPS04 MPH04		3.5	●		18 – 36 36 – 75	● ●	●			● ●			● ●	● ●	● ●	83									
↓	MPP03	DIP-24	3	●			● ●	● ●			● ●			● ●	● ●	● ●	87	1.25				0.80	0.40			
↓	MPP06		6	●		4.5 – 9 9 – 18	● ●	● ●			● ●			● ●	● ●	● ●	89									
↓	MPK06		6	●		18 – 36 36 – 75	● ●	●			● ●			● ●	● ●	● ●	87									
↓	MPP10		10	●			● ●	● ●			● ●			● ●	● ●	● ●	89									
↓	MPP03W		3	●			● ●	● ●			● ●			● ●	● ●	● ●	87									
↓	MPP06W		6	●		9 – 36 18 – 75	● ●	● ●			● ●			● ●	● ●	● ●	89									
↓	MPP10W	10	●			● ●	● ●			● ●			● ●	● ●	● ●	89										
↓	MPM15	1.6"x1"	15	●		9 – 18 18 – 36	● ●	●			● ●			● ●	● ●	● ●	90	1.60				1.00	0.40			
↓	MPM20		20	●		36 – 75	● ●	●			● ●			● ●	● ●	● ●	90									
↓	MPM15W		15	●		9 – 36	● ●	●			● ●			● ●	● ●	● ●	89.5									
↓	MPM20W		20	●		18 – 75	● ●	●			● ●			● ●	● ●	● ●	89									
↓	MPD30	2"x1"	30	●		9 – 18 18 – 36 36 – 75	● ●	●			● ●			● ●	● ●	● ●	90.5	2.00				1.00	0.40			
↓	MPD30W		30	●		9 – 36 18 – 75	● ●	●			● ●			● ●	● ●	● ●	90.5									
↓	MPQ60W	1/4 Brick	60	●		9 – 36 18 – 75	● ●	● ●			● ●			● ●	● ●	● ●	92.5	4.5				8		2.28	1.45	0.50

【お問い合わせ先】

JEMCO

株式会社ジェムコ

大阪本社 TEL : 06-6338-8566

東京 TEL : 080-6449-9194

名古屋 TEL : 0587-96-1970

URL : <http://www.jemc.co.jp/>

E-Mail : inf@jemc.co.jp